



NOTES:

STORM INLET SEDIMENT TRAPS SHALL BE PLACED IN ALL PROPOSED CURB INLETS AND AREA INLETS AS DIRECTED BY THE CITY OF CEDAR PARK'S PROJECT REPRESENTATIVE.

THE LATERAL BRACING SHALL BE PLACED IN A MANNER AS TO ADEQUATELY SECURE THE FILTER FRAME TO THE SIDE OF THE INLET, INSURING THE PROPER FUNCTION OF THE SEDIMENT TRAP.

FILTER FABRIC MAY BE IDENTICAL TO THAT SPECIFIED AS "TEMPORARY SEDIMENT CONTROL FENCE". OTHER MATERIAL MAY BE USED UPON APPROVAL OF THE CITY OF CEDAR PARK'S PROJECT REPRESENTATIVE.

THE "STORM INLET SEDIMENT TRAPS" SHALL BE INSTALLED UPON COMPLETION OF THE PROPOSED INLET WALLS OR AS DIRECTED BY THE CITY OF CEDAR PARK'S PROJECT REPRESENTATIVE.

THE CONTRACTOR WILL BE REQUIRED TO PERFORM PERIODIC MAINTENANCE OF THE SEDIMENT TRAP AND REMOVE ACCUMULATED SILT AS DIRECTED BY THE CITY OF CEDAR PARK'S PROJECT REPRESENTATIVE.

"STORM INLET SEDIMENT TRAPS" SHALL REMAIN IN PLACE UNTIL CONSTRUCTION OF THE PROPOSED INLET DECK BEGINS.

ALL WOOD SHALL BE PRESSURE TREATED.

STORM INLET SEDIMENT TRAP

CITY OF CEDAR PARK
PUBLIC WORKS ENGINEERING

STANDARD DETAIL
STORM INLET SEDIMENT TRAP

DARWIN MARCHELL, P.E.

ADOPTED: 01/02/01

SCALE: NTS

INITIAL: